

Contactor Panel with Dusk-to-Dawn Photocell Sensor



FEATURES & BENEFITS

10, 20, 30 or 40 Amp CapacityNEMA 4X Non-metallic EnclosurePreassembled, Prewired, Ready-To-InstallFixed Position or Adjustable Angle Sensor

Integral Dusk-to-Dawn Photocell Sensor

1-Pole, 2-Pole or 3-Pole Contactor

120/240VAC, 50/60 Hz Operation

UL/CSA Approved Components

Can Be Wall or Pole Mounted

Shown with Fixed Position Photocell Sensor

DESCRIPTION

LLCP Series Low Cost Contactor Panels with Dusk-to-Dawn Photocell Sensor are pre-configured, pre-wired and ready to install. The series provides a fast, economical solution for controlling 120 or 240VAC lighting applications. Each unit comes pre-wired and includes a built-in dusk-to-dawn photocell sensor, control contactor and NEMA 4X weatherproof non-metal enclosure with a gasketed hinged door and closure buckles. Applications include sporting field lighting, security lighting, business sign lighting, marina dock lighting, parking lot lighting and many other uses.

APPLACATIONS

Parking Lot Lighting Control - Security Lighting
Driveway & Pathway Lighting - Business Sign Lighting
Boat Dock Lighting - Landscape Lighting Control



General Specifications

Operating Temperature: -40 to 140 °F (-40 to 60 °C)

Contactor Type: Definite Purpose

Contactor Rating: UL/CSA Approved

Contactor Coil Control Voltage: 120VAC 50/60 Hz Control Type: Photocell Sensor (Dusk-to-Dawn)

Contactor Pole Connections: Box Lugs and Spade Terminals

Contactor Pole Load Capacity: See Model Tables

Enclosure: UL Listed, NEMA 4X, PC/PBT Blended Plastic

Enclosure Dimension: 5.9 x 5.9 x 3.6"

Installation: Wall or Pole Mounted, For Outdoor or Indoor Use.


Models with Fixed Position Photocell Sensor

Model Number	Contactor Pole Load Capacity	Contactor Poles
LLCP-10A-1	10 Amp, 120/240VAC 50/60 Hz	1
LLCP-20A-1	20 Amp, 120/240VAC 50/60 Hz	1
LLCP-30A-1	30 Amp, 120/240VAC 50/60 Hz	1
LLCP-40A-1	40 Amp, 120/240VAC 50/60 Hz	1
LLCP-10A-2	10 Amp, 120/240VAC 50/60 Hz	2
LLCP-20A-2	20 Amp, 120/240VAC 50/60 Hz	2
LLCP-30A-2	30 Amp, 120/240VAC 50/60 Hz	2
LLCP-40A-2	40 Amp, 120/240VAC 50/60 Hz	2
LLCP-10A-3	10 Amp, 120/240VAC 50/60 Hz	3
LLCP-20A-3	20 Amp, 120/240VAC 50/60 Hz	3
LLCP-30A-3	30 Amp, 120/240VAC 50/60 Hz	3
LLCP-40A-3	40 Amp, 120/240VAC 50/60 Hz	3

For Model with Adjustable Angle Sensor ad "-AS" to part number. Example: LLCP-20A-2-AS



Adjustable Angle Photocell Model



Pre-wired Control Contactor

© 2014 :: Imagine Instruments LLC :: 4500 Williams Drive, Ste 212-318 :: Georgetown, TX 78633 :: p. 512.778.6850 e-mail: info@imagineinstruments.com :: www.ImagineInstruments.com

Note: Continued product improvements make specifications subject to change without notice. Check www.imagineinstruments.com for the latest product information and updates

Released: 15 January, 2015 :: Rev: A